

HOT FLUSH FEATURES & SPECIFICATIONS

	4 GPM	9 GPM	15 GPM	20 GPM	40 GPM	60 GPM	80 GPM
18 GAUGE STAINLESS STEEL CABINET	X	X	X	X	X	X	X
VISUAL INSPECTION FILTRATION SYSTEM: <i>28 MICRON CHECKABLE SCREEN</i>	4"SCREEN	6" SCREEN	8" SCREEN	10" SCREEN	(2)10" SCREENS OR 12" Coil	(2)10" SCREENS OR 12" Coil	(2)10" SCREENS OR 14" Coil
<i>10 MICRON TO 50 MICRON RESERVOIR FILTER</i>	X	X	X	X	X	X	X
<i>PATENTED FLUSHING OPERATION COMPUTER CONTROLLED VALVE, COMPLETELY REVERSES FLOW FOR ¼ SECOND, EVERY 3 SECONDS</i>	X	X	X	X	X	X	X
HEATER	1250 WATT	6K WATT	6-8K WATT	8-10K WATT	14-20K WATT	14-24K WATT	20-30K WATT
**POWER REQUIREMENT	120V A/C	240V A/C	240-480V A/C	240-480V SP A/C	240-480V 3P A/C	240-480V 3P A/C	240-480 3P A/C
CURRENT	16 AMPS	32 AMPS	40 AMPS	50/25 AMPS	70/35 AMPS	70/35 AMPS	80/40 AMPS
**PUMP FLOW RATE	4 GPM	9 GPM	15 GPM	20 GPM	40 GPM	60 GPM	80 GPM
120 PSI AUTO AIR INJECTION	X	X	X	X	X	X	X
DIRTY FILTER-AUTO SHUT OFF	X	X	X	X	X	X	X
FLOW METER	X	X	X	X	X	X	X
4 PRESET AUTO SHUT OFF TIMERS	X	X	X	X	X	X	X
AIR HOSE & NOZZLE	X	X	X	X	X	X	X
DIGITAL TEMPERATURE GAUGE	X	X	X	X	X	X	X
PRESSURE GAUGE	X	X	X	X	X	X	X
CLEAN OUT SWITCH, PURGES SYSTEM	X	X	X	X	X	X	X
PRESET OIL PRESSURE: 80 PSI MAX	X	X	X	X	X	X	X
RESERVOIR CAPACITY: GALLONS	4	4	8-20	8-40	20-60	30-80	40-100
OPERATING TEMPERATURE	OPERATING TEMPERATURE: 0-190 DEGREES - VARIABLE FOR ALL MODELS						
OVERALL DIMENSIONS:	H35-1/2" X W29"X D19"	H35-1/2" X W29"X D19"	VARIABLE	VARIABLE	VARIABLE	VARIABLE	VARIABLE
AIR REQUIREMENT: 120 PSI	X	X	X	X	X	X	X
WARRANTY:	X	X	X	X	X	X	X
LASER PARTICLE COUNTER	OPTION IS AVAILABLE FOR ALL MODELS						